

WUQIANG JINGRUI FIBERGLASS PRODUCTS CO.,LTD

武强县京瑞玻纤制品有限公司

NAME: FIBERGLASS INSECT SCREEN

Specs: Gray 18\*16mesh

| Test Item   | Units     | Standard           | Test result | Determinant |
|---|-----------|--------------------|-------------|-------------|
| Tension of Warp   | N/Inch    | $\geq 320N(18*16)$ | 340         | Eligibility |
| Tension of Weft   | N/Inch    | $\geq 280N(18*16)$ | 304         | Eligibility |
| Width   | CM        | +13/-0MM           | 10          | Eligibility |
| Weight  | g/m2      | $\geq 110G$        | 110         | Eligibility |
| Density of Warp   | Mesh/Inch | $\leq 0.5MESH$     | 18          | Eligibility |
| Density of Weft   | Mesh/Inch | $\leq 0.5MESH$     | 16          | Eligibility |
| Ignition loss   | %         | $\geq 50\%$        | 55          | Eligibility |
| Pvc coating   | %         | $64\% \pm 1\%$     | 65%         | Eligibility |
| Glass Yarn  | %         | $34\% \pm 1\%$     | 35%         | Eligibility |
| Flammability(the time from leaving flame to extinguish) | seconds   | $\leq 10$          | 3           | Eligibility |
| appearance  | Good      |                    |             |             |

Test temperature: 22°C RH: 55%

武强县京瑞玻纤有限公司  
WUQIANG JINGRUI FIBERGLASS PRODUCTS CO., LTD